



LINK Multi-Core cable, 8 cores Double Shield

FEATURES AND BENEFITS

LINK Multi-cores single shield cable support internal wiring and design for installation requiring flexible conductor to fulfill measuring control and command application i.e. computer interconnect, control circuit, industrial equipment control, suitable for EIA RS-232 application.

LINK Multi-Core cable in accordance with

UL2464, UL2576, UL2919, UL444, CSA and RoHS Compliant

ORDER INFORMATION

Part Number	Description	Color	Length	Package
CB-0248	Multi-Core Cable, 8 Core Double Shield, 24AWG	Gray	500 m.	Roll

ELECTRICAL CHARACTERISTIC

Rating Temp. & Voltage	80°C 300V
Max. Conductor DC Resistance	89.1 Ohm/km @20°C
Min. Insulation Resistance	3 Mega Ohm/km @20°C
Dielectric Strength between pairs	DC 1.5 KV/Minute
Conductor Capacitance	91 pF/m
Characteristic Impedance	65 Ohm



CABLE CONSTRUCTION

Conductor	No. of conductor		8 core
	Size		24 AWG
	Cond. Material		Stranded Tinned Anneal Copper
	Stranded wire no./Diameter		7/0.20 ±0.01 mm
Insulation	Thickness		0.25 ±0.03 mm
	Diameter		1.15 ±0.05 mm
	Material		Lead Free SR-PVC
	Color		White ,Red ,Green ,Black ,Blue ,Brown ,Orange ,Yellow
Shielded	Filler		Polypropylene(PP)
	AL/P-Foil		0.025 mm
	Braid Wire	Material	Tinned Anneal Copper
		Wire no./Diameter	112/0.12 mm.
		Coverage	76%
	Drain Wire	Material	Tinned Anneal Copper
Wire no./Diameter		7/0.16 mm	
Jacket	Thickness		1.10 ±0.06 mm
	Overall Diameter(O.D.)		6.3 ±0.3 mm
	Material		FR-PVC
	Color		Gray

PHYSICAL PROPERTIES

Tensile Strength	13.8 MPa (≈ 2002 PSI)
Min. Bending Radius	8 x O.D. (50.40 mm)
Heat Shock Test	121±1°C x 1 hr (No Crack)
Cold Shock Test	-20±1°C x 4hr (No Crack)
Operating Temperature Range	-10°C to +60°C

-END OF SPECIFICATION-



Specifications subject to change without notice. Revised 1/2018
©Copyright 2018 are Trademark and all rights reserved.