

# WALL RACK

## G1 SERIES



**19"GERMANY**<sup>®</sup>  
EXPORT RACK



Master Key w/logo




Roller



Mounting Pole



Hinge w/logo



Two Plies Steel



A



B

### FEATURES

- ◆ **Designed and Manufactured** to comply with the standard of ANSI/EIA-310D-1992 (Rev. EIA-310C), IEC60297-1, IEC60297-2, BS5954 Part : 2, DIN 41494, 19" Standard.
- ◆ **Three sections** design Front Door, Center Part and Back Base Box.
- ◆ **Produced** from Electro-Galvanized Sheet Steel thickness of 1.2 mm. Mounting Pole, made of 2.0 mm.
- ◆ **Mounting Pole** were designed to be L-shape angle in order to increase the strength. Punching of square mounting hole 10 x 10 mm. They can be adjusted in/out freely to meet customer's needs. And provide the U-height screened on the mounting pole.
- ◆ **Front Door** (for model G1-XXXX) is the steel frame with acrylic 5.0 mm. thickness with film protection and the width of acrylic is 38 cm. (the height is being influenced by the size of the rack) Door edge is bore with gray dust-proof rubber seal (3 fins). Top the front door has embossed trademark. Security locks with 19" Germany Master Key. For model G1-XXXXP is the steel door with perforated capsule ventilation 50% of door's area.
- ◆ **Center Part** has sliding rail for adjusting the mounting pole throughout the whole depth of this part. The bottom equipped with rollers. The top has a pre-punch fan pattern for 1 to 3 Fans and on the both side has ventilation grills. Security lock with 19" Germany Master Key which is the same set as the front door.
- ◆ **Back Base Box** has the clip 10 x 10 cm. for cable access in the top and bottom. Hanger slot for screw on the back part is the two plies steel with 2.4 mm. thickness.
- ◆ **Hinge** is 19" Germany Export Rack products made from 3 pieces of high strength special PVC (ABS), rust-free and without any interfering noise. The reversibility of front and rear door opening from left of right by adjusting at one screw nut of hinge.
- ◆ **New Shine Light Gray** Two-Tone color by Electrostatic Powder Coating paint for scratch resistance.
- ◆ **Screw Set** compose of Screws, Captive nuts, Plastic washer; by each were coated with nickel and M6 thread system.
- ◆ **Manufacturing and Distribution** by ISO 9001:2008 Company.

### Options

Color	*Black or other
Thickness	1.6 mm or other
Pole	4 Poles
Grounding Kit	2.5 mm

### Deliverly with

- 3 Master keys with trademark and number on the keys.
- 4 sets of wall mounting screw.
- Set of nut and screw according to the size of Rack.

### ORDERING INFORMATION **W=Width 600 mm. Standard**

1U = 44.45 mm.	Overall Height (mm.)	Order No. of Different Depth (mm.)			Figure
		D = 400	D = 500	D = 600	
6U	320	G1-60406	G1-60506	G1-60606	A
9U	455	G1-60409	G1-60509	G1-60609	
12U	590	G1-60412	G1-60512	G1-60612	
6U	320	G1-60406P	G1-60506P	G1-60606P	B
9U	455	G1-60409P	G1-60509P	G1-60609P	
12U	590	G1-60412P	G1-60512P	G1-60612P	

\* Order No. for Black Color : G1-XXXXB

Sample : G1-60609B Wall Rack 9U, 60 x 60 cm., Black Color

# WALL RACK

## G2 SERIES



**19"GERMANY**<sup>®</sup>  
EXPORT RACK



Master Key w/logo




Roller



Mounting Pole



Hinge w/logo



Two Plies Steel



### FEATURES

- ◆ **Designed and Manufactured** to comply with the standard of ANSI/EIA-310D-1992 (Rev. EIA-310C), IEC60297-1, IEC60297-2, BS5954 Part : 2, DIN 41494, 19" Standard.
- ◆ **Three sections** design Front Door, Center Part and Back Base Box.
- ◆ **Produced** from Electro-Galvanized Sheet Steel thickness of 1.2 mm. Mounting Pole, made of 2.0 mm.
- ◆ **Mounting Pole** were designed to be L-shape Angle in order to increase the strength. Punching of square mounting hole 10 x 10 mm. They can be adjusted in/out freely to meet customer's needs. And provide the U-height screened on the mounting pole.
- ◆ **Front Door** is the steel frame with Acrylic 5.0 mm. thickness with film protection and the width of acrylic is 38 cm. (the height is being influenced by the size of the rack) which is perforated capsule surrounding the acrylic. Door edge is bore with gray dust-proof rubber seal (3 fins). Top the front door has embossed trademark. Security locks with 19" Germany Master Key.
- ◆ **Center Part** has sliding rail for adjusting the mounting pole throughout the whole depth of this part. The bottom equipped with rollers. The top has a pre-punch fan pattern for 1 to 3 Fans and on the both side has ventilation grills. Security lock with 19" Germany Master Key which is the same set as the front door.
- ◆ **Back Base Box** has the clip 10 x 10 cm. for cable access in the top and bottom. Hanger slot for screw on the back part is the two plies steel with 2.4 mm. thickness.
- ◆ **Hinge** is 19" Germany Export Rack products made from 3 pieces of high strength special PVC (ABS), rust-free and without any interfering noise. The reversibility of front and rear door opening from left of right by adjusting at one screw nut of hinge.
- ◆ **New Shine Light Gray** Two-Tone color by Electrostatic Powder Coating paint for scratch resistance.
- ◆ **Screw Set** compose of Screws, Captive nuts, plastic Washer; by each were coated with nickel and M6 thread system.
- ◆ **Manufacturing and Distribution** by ISO 9001:2008 Company.

### Options

Color	*Black or other
Thickness	1.6 mm or other
Pole	4 Poles
Grounding Kit	2.5 mm

### Deliverly with

- 3 Master keys with trademark and number on the keys.
- 4 sets of wall mounting screw.
- Set of nut and screw according to the size of Rack.

### ORDERING INFORMATION **W=Width 600 mm. Standard**

1U = 44.45 mm.	Overall Height (mm.)	Order No. of Different Depth (mm.)		
		D = 400	D = 500	D = 600
6U	320	G2-60406	G2-60506	G2-60606
9U	455	G2-60409	G2-60509	G2-60609
12U	590	G2-60412	G2-60512	G2-60612

\* Order No. for Black Color : G2-XXXXB

Sample : G2-60609B Wall Rack 9U, 60 x 60 cm., Black Color