

# INFORMA 600E

4 Channels, 24 Telephone Numbers, PSTN Only



## General Features

Calling up to 24 phone numbers, of 20 digits each. These numbers are independently assigned to each of the 4 channels

Messages can be repeated up to 9 times

LCD display with 16 alphanumeric characters of telephone numbers and stored functions

Storage of the last 64 events with date, time, enabled inputs, and phone numbers which have answered the call

Simple and quick keypad programming through guided menu

Failure output caused by telephone line cut-off, low battery and failed calls  
Local activation by means of a keypad with 2 logic outputs

Direct recording with immediate hearing of the 5 messages (maximum duration 15 seconds each) divided into 4 alarm messages and 1 failure messages

Alarm cancellation input

Programmable call delay from 1 to 240 seconds

## INFORMA 600E

Parameter	Description
Power Supply	11.5~13.8 VDC
Power Consumption: Standby	90 mA
Maximum	120 mA
Alarm Inputs	4, N.C., N.O. and Not Used.
Outputs	4 Logic Outputs
20 Called Digit Phone Numbers	24
Total Recordable Messages	5 Messages of a Maximum Duration of 15 Sec.
Programming	Keypad
Display	2-Line 16-Character LCD
Keypad	16 Alphanumeric Keys
Auto-Protection	Anti-Opening and Anti-Removal
Events Memory	64 Events with Time and Date
Operating Temperature	-20°C ~ 55°C (-4°F ~ 131°F)
Weight	579g

