



Aerial Straight Joint Closure

UF-3042S FTTH Aerial Straight Joint Closure is suit for inline, branch closure, the scope of application is aerial mounting, wall mounting.

Applications

- > Suitable for bunchy fibers.
- Aerial mounting, Wall mounting
- > It's especially applicable to FTTH optical fiber distribution.

Features

- The closure adopts horizontal mechanical sealing and advanced internal structure design, which was made from high grade Polycarbonate.
- 6 ports Round type (3.5mm) or Flat type (2x3mm) drop cable both ends in and out, which is suitable for straight-through the fiber cable.
- The closure is spacious enough for winding and storing fibers.
- The patented sealing structure keep good sealing performance after re-entry and re-using.
- Support IP65 Standard
- Easy open and close of closure with clip lock.
- Max. 144 cores Fusing Splice available.

Capacity

Outside dimension : 350x210x113 mm

Weight (w/out box) : 1,920g

Main cable ports : 4 ports, Φ8mm – Φ16mm Drop cable ports : 16 ports, 3.5mm or 2x3mm

Max. capacity of : Bunchy 144 cores

Splice Trays : 24F Per Trays, Max 6 Trays

Fiber Optic Splice Closure





Order Information

Descriptions	Part Number
FTTH Aerial Straight Joint Closure 24-48 Core	UF-3042S
FTTH Aerial Straight Joint Closure 24-48 Core (TOT Project)	UF-3042S-TOT

Accessories

Hanging hook Labeling paper Cable tie Seal tape & Oli Insulation tape Installation manual Heat shrinkable protective sleeve Buffer tube Sandpaper Earthing wire Cleaning tissue (Alcohol tissue)

Structural Drawing



