

F.O. INDOOR/OUTDOOR, PLASTIC TERMINAL, w/ADAPTER & ACC.

LINK F.O. INDOOR/OUTDOOR, PLASTIC TERMINAL
DESCRIPTION

This distribution box terminates up to 2 fiber optic cables, offers spaces for splitters and up to 48 fusions, UF-4125A-UPC allocates 12 SC up to 24 SC adapters and working under both indoor and outdoor environments. It is a perfect cost-effective solution-provider in the FTTx networks.

FEATURES

- ✚ ABS material used ensures the body strong and light.
- ✚ Water-proof design for outdoor uses.
- ✚ Easy installations: Ready for wall mount – installation kits provided.
- ✚ Adapter slots used – No screws and tools needed for installing adapters.
- ✚ Ready for splitters: designed space for adding splitters.
- ✚ Space saving! Double-layer design for easier installation and maintenances:
- ✚ Lower layer for splitters and over length fiber storage.
- ✚ Upper layer for splicing, cross-connecting and fiber distribution.
- ✚ Cable fixing units provided for fixing the outdoor optical cable.
- ✚ Protection Level: IP65.
- ✚ Accommodates both cable glands as well as tie-wraps
- ✚ Lock provided for extra security.


SPECIFICATIONS

Dimensions (W*H*D)	300mm*380mm*100mm
Included	12 SC adapter
Adapter Capacity	24 SC simplex adapters
Number of Cable Entrance/Exit	2 cables (max diameter 20mm) / 28 simplex cables
Weight	2 KG

Operation Conditions	
Temperature	-40°C to 60°C
Humidity	93% at 40°C
Air Pressure	62kPa – 101kPa

