


# BUFFER TUBE 900 μm



LINK Buffer tube 900 μm can be employed as buffering material and provide additional protection for use with 250 μm fiber

## DESCRIPTION / APPLICATION

- Protect bare fiber in any situation against mechanical damage during handling and installation.
- Bare fiber can be easily installed more than 5 meters.
- High resistance to creep, impact, and flex fatigue; flexibility at low temperature; and good retention of properties at elevated temperatures.



Part Number	Description	Dimension (μm)	Color
UFC6200	Buffer tube 900 μm	900 μm	Clear

# 12 FIBER SPLICING TRAY

## DESCRIPTION / APPLICATION

- For use with all LINK rack mount enclosure and wall mount enclosure.
- Made from aluminum and accommodated 12 fusion splicing per tray.
- Protects and manages fiber splices
- Minimum fiber bending radius is maintained
- Used for multimode and single mode



Part Number	Description	Dimension (mm.)	Color
SV-2256	12 Fiber Splicing Tray	140 x 125 x 10	Light Grey

# FUSION PROTECTOR SLEEVE

## DESCRIPTION / APPLICATION

- For use with splicing tray
- Protects fiber splices
- Clear outer tube and Stainless steel needle.



Part Number	Description	Dimension (mm.)	Color
SV-2252A	Fusion Splice Protector Sleeve, 60 mm., Slim Type	2.5 x 60	Clear
SV-2252	Fusion Splice Protector Sleeve, 60 mm.	2.8 x 60	Clear
SV-2251	Fusion Splice Protector Sleeve, 40 mm.	2.5 x 40	Clear

# OTDR DUMMY CABLE BOX

Designed to aid in the testing of fiber optic cable when using an OTDR. Launch Fiber Box is used with Optical Time Domain Reflectometers (OTDR's) to help minimize the effects of the OTDR's launch pulse on measurement uncertainty. Available in many different configurations and fiber lengths.

## SPECIFICATION

- Operating Temperature : -40°C to +50°C
- Typical Loss : <1dB@1310nm for 1000 meters
- Standard Attachment : Insert Return Loss Report  
OTDR Test Report  
3D Test Report (Grade A only)



## PART NUMBER : UF - [A] - [B] - [C] - [D]

A = Input Connector	B = Output Connector	C = Fiber	D = Length
FC - FC/UPC	FC - FC/UPC	9 - 9/125 (OS2)	0.5 - 0.5 km
SC - SC/UPC	SC - SC/UPC	6 - 62.5/125 (OM1)	1.0 - 1.0 km
ST - ST/UPC	ST - ST/UPC	5 - 50/125 (OM2)	2.0 - 2.0 km
FCA - FC/APC	FCA - FC/APC	4 - 50/125 (OM3)	-
SCA - SC/APC	SCA - SC/APC	-	-
LC - LC/UPC	LC - LC/UPC	-	-

**For Example :** Single mode fiber, input FC/UPC, output SC/UPC, 1000 meters UF-FC-SC-9-1.0  
**Remark :** Other special fiber or connectors are available upon request.