

OUTDOOR STEEL CABINET (Wall Mount)



Link for the perfect Cabling

Outdoor steel cabinet which is designed for external use. Painting with 100 % UV-resistance paint. Structure is designed for water protection with closed system and roof for fast drainage. Hook available outside the cabinet for hanging, Cable patchway is available at the back-side with special water, dust-protection rubber ring, horn-shaped swing handle and locking system with key and shutter. Grounding all cabinet connect between front door and structure. Made from electro-galvanize steel 1.5 mm thickness. water proof performance IP55, UV protection.



Outdoor/Wall mount



Inside

ORDER INFORMATION

LINK P/N	Tel. Capacity (pair)	BMF used (option)	Dimension WxHxD (cm.)
UL-7061	50 - 60	1 x 6 pos.	25 x 33 x 15
UL-7111	100 - 110	1 x 11 pos.	25 x 45 x 15
UL-7112	200 - 220	2 x 11 pos.	45 x 45 x 15
UL-7113	300 - 330	3 x 11 pos.	65 x 45 x 15
UL-7222	400 - 440	2 x 22 pos.	45 x 73 x 15
UL-7272	500 - 540	2 x 27 pos.	50 x 88 x 15
UL-7223	600 - 660	3 x 22 pos.	65 x 73 x 15

MAIN DISTRIBUTION OPEN FRAME

Main Distribution Open Frame for telephone system and designed by a German engineer under the German Standard. The Main Distribution Frame is particularly durable, spacious and ideal for use. Manufacture from special electro-galvanized steel 1.5 mm. thickness. Open Frame design for easy installation, save space and easy maintenance.

ORDER INFORMATION

Type/Description	Dimension WxHxD (cm.)	Tel. Capacity (pair)	LINK P/N
Main Distribution Frame Single	28.5 x 204 x 15.1	700 - 770	UL-7371S
Main Distribution Frame Double	56.5 x 204 x 15.1	1400 - 1540	UL-7372S

Remark :

- Back mount frame 33 and 44 pos. are recommend to install on each frame.

Type/Description	Dimension WxHxD (cm.)	Tel. Capacity (pair)	LINK P/N
Main Distribution Frame Single, Profile Rod	28.5 x 204 x 15.1	700 - 770	UL-7377
Main Distribution Frame Double, Profile Rod	56.5 x 204 x 15.1	1400 - 1540	UL-7378

Single Frame

Double Frame

