

OUTDOOR STEEL CABINET (Wall Mount)



Outdoor Steel Cabinet was made from Electro-galvanized steel 1.5mm thickness and designed for outdoor installation which is 100% UV-resistance painting for UV protection. The structure was designed for waterproof (IP55 Standard) with closing system and roof to fast draining. There are hook at the top of cabinet for mounting. The cabinet can be wiring from the rear-side, also have water-protection, dust-protection rubber ring, horn-shaped swing handle with key locking system and shutter. All cabinets size have grounding which connect between frame and front door.



Outdoor/Wall mount



Inside

ORDER INFORMATION

LINK P/N	Tel. Capacity (pair)	BMF used (option)	Dimension WxHxD (cm.)
UL-7061	50 - 60	1 x 6 pos.	25 x 33 x 15
UL-7111	100 - 110	1 x 11 pos.	25 x 45 x 15
UL-7112	200 - 220	2 x 11 pos.	45 x 45 x 15
UL-7113	300 - 330	3 x 11 pos.	65 x 45 x 15
UL-7222	400 - 440	2 x 22 pos.	45 x 73 x 15
UL-7272	500 - 540	2 x 27 pos.	50 x 88 x 15
UL-7223	600 - 660	3 x 22 pos.	65 x 73 x 15

MAIN DISTRIBUTION OPEN FRAME

Main Distribution Open Frame was designed by German engineer under the German Standard for telephone system. The Main Distribution Frame are especially durable, extensive and premium quality for usability. Frame was made from Electro-galvanized steel 1.5mm thickness. The open frame was designed for saving space, easy installation and maintenance.

ORDER INFORMATION

LINK P/N	Type/Description	Tel. Capacity (pair)	Dimension WxHxD (cm.)
UL-7371S	Main Distribution Frame Single	700 - 770	28.5 x 204 x 15.1
UL-7372S	Main Distribution Frame Double	1400 - 1540	56.5 x 204 x 15.1

Remark :

- Back mount frame 33 and 44 pos. are recommend to install on each frame.

LINK P/N	Type/Description	Tel. Capacity (pair)	Dimension WxHxD (cm.)
UL-7377	Main Distribution Frame Single, Profile Rod	700 - 770	28.5 x 204 x 15.1
UL-7378	Main Distribution Frame Double, Profile Rod	1400 - 1540	56.5 x 204 x 15.1

Single Frame

Double Frame

