
Wireless Vanishing Door/Window Contact

WS4975W

Installs in Seconds & Virtually Vanishes

By far the smallest wireless door/window contact currently available in the world, the wafer-thin profile of the WS4975W provides a streamlined, practically non-existent look once installed. The contact can be easily mounted to a window frame with double-sided tape, eliminating the need for drilling. This not only reduces installation times but also retains the integrity of window warranties. A generous magnet gap of 16 mm (5/8") easily accommodates larger door or window frames. The WS4975W is built with reliable 433 MHz technology and is compatible with all current DSC wireless receivers.





Product Features:

- Wafer-thin profile
- Easy and reliable installation
- Long-life lithium battery included
- ▶ 16 mm (5/8") maximum magnet gap
- Reliable 433 MHz technology
- Double-sided tape (included)
- Case tamper
- RoHS compliant
- Temperature rated at -10° C to 50° C
- CE approved



Wireless Vanishing Door/Window Contact



Value Added

Significantly smaller than competitor door/window contacts, the WS4975W is housed within a compact casing that allows it to be used for the tightest-fitting installations. Once installed, the contact is inconspicuous and complements the décor of most homes. It is built with reliable 433 MHz technology, uses a long-life lithium battery and is compatible with all current DSC wireless receivers.



Ordering Information:		
WS4975W	Wireless Vanishing Door/Window Contact	
	(EU Baud Rate)	

Compatibility

The WS4975W is compatible with the following receivers:

PowerSeries[™] Wireless Receivers RF5132-433W/PC5132-433W all versions and RF5108-433W

PowerSeries RFK Keypads (RFK5500/RFK5501/RFK5516/RFK5508)

Fixed-Message LCD Keypad with Integrated Wireless Receiver RF5501-433W

Specifications

Dimensions	57 mm x 25.4 mm x 4.8 mm (2 ^{1/4} " x 1" x 3/16")
Battery	CR2032 (3 V Lithium)
Battery Life	5 Years (Typical)
Operating Temperature	-10 to 50°C (14-122 °F)
Operating Humidity	5-93% RH





For product information www.dsc.com Product specifications and availability subject to change without notice. Certain product names mentioned herein may be trade names and/or registered trademarks of other companies. ©2007 2007-04

Distributed by: